

RACKOM- 42U Floor Standing Server Rack

Brand- RAckOm

- Usability- Network Switches/Routers/ DVR/ Audio- Visual Equipment/Broadcasting Equipment /Servers
- Front Door- Glass Door Or Full perforated With Lock
- Rear door- Half Perforated and Full Perforation Steel Door With Lock
- Side Panels- Removable With Slam Latch and Lockable Provision
- Cable Entry Cut-Top/ Bottom
- 4 Pair Heavy Duty (2.0mm) Depth Support Channel Fitted On Front & Rear Pillar
- 2 Pair Heavy Duty (2.0mm) Vertical Mounting Rail Channel Fitted On Front & Rear Pillar
- Cooling Option- 4 fan Provision mounted on Top Panel
- Load Bearing Capacity up to 600 to 1000 KG
- Construction- Dismantle Construction Overall 1.2mm Thick (18 gauge), Load Bearing angles are 2 MM
- Power Distribution Unit- Horizontal Vertical Optional
- Cable Management- Horizontal & vertical
- Sliding Tray For Equipment and Keyboard Optional
- Color- light Grey Powder Coated (RAL 7035) and RAL 9005 Black (as per Requirement)

Part No.	Height in U	Overall Height with Castor/Leg	Usable Height	Overall Width	Usable Width	Overall Depth	Usable Depth
RSFS0042-001 (42U 600x600)	42U	2100mm (82.67 Inch)	1866.9mm (73.5" INCH)	600mm	482.6mm 19 Inch	600mm	480mm (18.89 inch)
RSFS0042-002 (42U 600x800)	42U	2100mm (82.67 Inch)	1866.9mm (73.5" INCH)	600mm	482.6mm 19 Inch	800mm	680mm (26.77 inch)
RSFS0042-003 (42U 600x1000)	42U	2100mm (82.67 Inch)	1866.9mm (73.5" INCH)	600mm	482.6mm 19 Inch	1000mm	880mm (34.64 inch)
RSFS0042-004 (42U 800x800)	42U	2100mm (82.67 Inch)	1866.9mm (73.5" INCH)	800mm	482.6mm 19 Inch	800mm	680mm (26.77 inch)
RSFS0042-005 (42U 800x1000)	42U	2100mm (82.67 Inch)	1866.9mm (73.5" INCH)	800mm	482.6mm 19 Inch	1000mm	880mm (34.64 inch)
RSFS0042-006 (42U 600x1200)	42U	2100mm (82.67 Inch)	1866.9mm (73.5" INCH)	600mm	482.6mm 19 Inch	1200mm	1080mm (42.51 inch)
RSFS0042-007 (42U 800x1200)	42U	2100mm (82.67 Inch)	1866.9mm (73.5" INCH)	800mm	482.6mm 19 Inch	1200mm	1080mm (42.51 inch)